

Data Sheet Pad-Ex® 01 P8 DZ2

Windows-Tablet-PC



ATEX



- Ex II 3G Ex ic IIC T4 Gc IP64
- Ex II 3D Ex ic IIIB T135°C Dc IP64

IECEX



- Ex ic IIC T4 Gc IP64
- Ex ic IIIB T135°C Dc IP64

SGS



- Northern America:
- Class I, II, III, Division 2, Groups A-G, T4, 135°C
- Class I, Zone 2, Group IIC T4

Japan



- Ex ic IIC T4 Gc



Technical Data	
Rugged features	- IP64 according to EN/IEC 60079-0 (ATEX/IECEX) - IP65 according to EN/IEC 60529 (industrial standard) - MIL-STD 810G certified (Drop, Shock, Vibration, Rain, Dust, Altitude, Freeze/Thaw, High/Low Temperature, Temperature Shock, Humidity) - MIL-STD 461 certified (Conduction, Radiation, Conducted Susceptibility, Radiated Susceptibility) - ANSI/ISA 12.12.01-2000, Class I, Division 2 4' drop 26 faces
Environment	- Operating Temperature: -10°C - 55°C (14°F - 131°F) - Storage Temperature: -10°C - 55°C (14°F - 131°F) - Operating Humidity: 5% to 95%
Operating System	Windows® 10 Pro (64 Bit)
CPU	Intel® Core™ i5-8250U (8th Gen.) 1.6GHz processor with Turbo Boost Technology up to 3.4GHz, 6MB cache
Memory	One DDR4 socket for 8 GB
Storage	M2-SATA SSD 256 GB (extended temperature range)
Display	• 29.46 cm / 11.6" (1920 x 1080) FHD LCD Panel • Capacitive Multi-Touch • Optical, sunlight-readable display
Audio	Speaker x1 / 70dB Microphone x1
Camera	2-MP front facing camera 5 MP rear camera with flashlight
Communication	- WWAN LTE + GPS Combo (optional) - Intel Wireless AC9260 802.11 a/b/g/n/ac - Bluetooth® 5.0
Data Collection	Optional 1-D / 2-D barcode scanner
VO Ports	- Two USB 3.0 • One headphone out / mic-in jack • One docking connector - One expansion connector for expansion modules • Two RF pass-through connectors for WWAN and GPS
Expansion Slots	One microSD card slot support SDHC and SDXC • One SIM card slot for WWAN data communication
Button	• Power • Volume • Windows touch button • Barcode / camera touch button • Programmable touch button
Battery	- One 3,950 mAh Li-Polymer battery pack: 7hrs - Optional (spare part) 7,800 mAh Li-Polymer battery pack: 14hrs
AC-Adapter	19V; 3.42 A; 65 W
Dimension / Weight	298 mm x 192 mm x 20 mm / 1.2 kg